

Bellagio 1



Application:

LUMINAIRE: 14" Diam. UV stabilized, clear textured polycarbonate glob with a heavy wall cast aluminum holder. Photo control optional.

Ballast: H.P.F. / C.W.A. up to 100 W. Metal halide, High Pressure Sodium, Mercury Vapor or Incandescent. Factory pre-wired.

LAMP HOLDER: Mogul or Medium Base Porcelain Socket

FINISH: Powder coat. Standard color Black. Custom colors also available, consult factory.

Job Information

Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	

DIMENSIONAL DRAWINGS



Height	Width	CFL	MH	HPS	EPA	Weight
30"	14"	42	100	100		12 lbs.

Isolux Curves

ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
<ul style="list-style-type: none"> • BEO1 	Type 5 <ul style="list-style-type: none"> • (T5) 	35w <ul style="list-style-type: none"> • (35) 50w <ul style="list-style-type: none"> • (50) 70w <ul style="list-style-type: none"> • (70) 100w <ul style="list-style-type: none"> • (100) 1x26w <ul style="list-style-type: none"> • (26) 1x32w <ul style="list-style-type: none"> • (32) 1x42w <ul style="list-style-type: none"> • (42) 	HPS <ul style="list-style-type: none"> • (HPS) Metal Halide <ul style="list-style-type: none"> • (MH) Compact Fluorescent <ul style="list-style-type: none"> • (CFL) Incandescent <ul style="list-style-type: none"> • (Incan) 	120 Volts <ul style="list-style-type: none"> • (120) 208 Volts <ul style="list-style-type: none"> • (208) 240 Volts <ul style="list-style-type: none"> • (240) 277 Volts <ul style="list-style-type: none"> • (277) 480 Volts <ul style="list-style-type: none"> • (480) Multi-Tap Ballast Factory wired at 277v unless otherwise specified.	Post Top Fitter Over 3" max. Round <ul style="list-style-type: none"> • (PTF) 	Black <ul style="list-style-type: none"> • (BK) Custom Color <ul style="list-style-type: none"> • (CC) Consult Factory	Internal 180 Deg. Shield <ul style="list-style-type: none"> • (180) Photo cell <ul style="list-style-type: none"> • (PC_v) Specify Voltage

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions