

# Santa Fe Round



## SPECIFICATIONS:

### Housing:

A weather tight unit fabricated from spun aluminum .080" thick Full gasketing keeps out insects and water.

### Optics:

Both the interior reflector and the polished parabolic distribution reflector are made of spun aluminum; they provide extremely high reflectivity to produce wide efficient light distribution

### Electrical Assembly:

HID Ballast constant Wattage Auto-Transformer High Power Factor Core and coil Type, Rated -20 Degrees Fahrenheit Staring Temperature. Integrally Mounted in the Luminaire and Completely Prewired. Each Ballast Assembly Is Thoroughly Tested Prior To Shipment. Ballast and Electrical Components Are "UL" Listed.

### Lamp Socket:

Porcelain Socket pulse rated at 5K & 600V for HPS, MH & PS lamps.

### Finish:

Chemically pretreated through a multiple stage washer, thermoset polyester textured Powder Coat. Oven baked at 400 degrees Fahrenheit to insure maximum adherence.

## Job Information

Project: \_\_\_\_\_ Date: \_\_\_\_\_


Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Cat. # \_\_\_\_\_

Lamp: \_\_\_\_\_ Volts: \_\_\_\_\_

Options & Accessories: \_\_\_\_\_

## DIMENSIONAL DRAWINGS



Fixture	Height	Diam.		Maximum Watts
SFE-1	21"	12"	12"	70w - 250w
SFE-2	32"	20"	20"	400w

## ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Wiring	Finish	Options
<ul style="list-style-type: none"> <li>SFE-1</li> <li>SFE-2</li> </ul>	<ul style="list-style-type: none"> <li>Symmetric (SYM)</li> </ul>	70w <ul style="list-style-type: none"> <li>(70)</li> </ul> 100w <ul style="list-style-type: none"> <li>(100)</li> </ul> 150w <ul style="list-style-type: none"> <li>(150)</li> </ul> 175w <ul style="list-style-type: none"> <li>(175)</li> </ul> 250w <ul style="list-style-type: none"> <li>(250)</li> </ul> 320w <ul style="list-style-type: none"> <li>(320)</li> </ul> 400w <ul style="list-style-type: none"> <li>(400)</li> </ul>	HPS <ul style="list-style-type: none"> <li>(HPS)</li> </ul> Metal Halide <ul style="list-style-type: none"> <li>(MH)</li> </ul> Pulse Start Metal Halide <ul style="list-style-type: none"> <li>(PS)</li> </ul> Compact Fluorescent <ul style="list-style-type: none"> <li>(CFL)</li> </ul> Consult Factory	120 Volts <ul style="list-style-type: none"> <li>(120)</li> </ul> 208 Volts <ul style="list-style-type: none"> <li>(208)</li> </ul> 240 Volts <ul style="list-style-type: none"> <li>(240)</li> </ul> 277 Volts <ul style="list-style-type: none"> <li>(277)</li> </ul> 480 Volts <ul style="list-style-type: none"> <li>(480)</li> </ul> Quad-tap <ul style="list-style-type: none"> <li>(MT)</li> </ul> Multi-Tap Ballast Factory wired at 277v unless otherwise specified.	Pole top Adaptor (PTA) 	Bronze <ul style="list-style-type: none"> <li>(BZ)</li> </ul> White <ul style="list-style-type: none"> <li>(WT)</li> </ul> Black <ul style="list-style-type: none"> <li>(BK)</li> </ul> Green <ul style="list-style-type: none"> <li>(GN)</li> </ul> Grey <ul style="list-style-type: none"> <li>(GY)</li> </ul> Custom Color <ul style="list-style-type: none"> <li>(CC)</li> </ul> Consult Factory	Photocell 120 - 277V <ul style="list-style-type: none"> <li>(PC__)</li> </ul> <ul style="list-style-type: none"> <li>(PR480)</li> </ul> Photocell & Shorting cap <ul style="list-style-type: none"> <li>(PSC)</li> </ul> House Side Light Shield <ul style="list-style-type: none"> <li>(HSS)</li> </ul> Wall Plate <ul style="list-style-type: none"> <li>(WP)</li> </ul>

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions