

WPR40



SPECIFICATIONS:

Housing:

Die-cast aluminum door has four captive stainless steel fasteners and can be removed from the die-cast aluminum housing. Provided with (4) .50" coin plugs for surface conduit run.

Lens:

Heat and shock resistant borosilicate glass. Available in clear or frosted white, both with radial prisms to provide superior illumination

Reflector:

specular white aluminum reflector .

Ballast Assembly:

HID ballast constant wattage auto-transformer high power factor core and coil type, rated -20 degrees Fahrenheit starting temperature. Integrally Mounted in the luminaire and completely prewired. Each ballast assembly is thoroughly tested prior to shipment. Ballast And Electrical Components are "UL" Listed.

Lamp Socket:

Porcelain socket pulse rated for HPS & MH lamps. lamp included.


Finish:

Attractive dark bronze, white, black polyester powder coated finish for excellent impact, corrosion and UV resistance

Job Information

Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	

DIMENSIONAL DRAWINGS



Height	Width	Depth	MH	HPS	EPA	Weight
15"	15"	9.25"	175	150	—	—

Optional Features



ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Face	Finish	Options
<ul style="list-style-type: none"> WPC40 	Forward Throw Wide <ul style="list-style-type: none"> (FTW) Type V <ul style="list-style-type: none"> (T5) 	50w <ul style="list-style-type: none"> (50) 70w <ul style="list-style-type: none"> (70) 100w <ul style="list-style-type: none"> (100) 175w <ul style="list-style-type: none"> (175) Compact Fluorescent <ul style="list-style-type: none"> (CFL) Consult Facotry	High Pressure Sodium <ul style="list-style-type: none"> (HPS) Metal Halide <ul style="list-style-type: none"> (MH) Compact Fluorescent <ul style="list-style-type: none"> (CF) 	120 Volts <ul style="list-style-type: none"> (120) 208 Volts <ul style="list-style-type: none"> (208) 240 Volts <ul style="list-style-type: none"> (240) 277 Volts <ul style="list-style-type: none"> (277) 480 Volts <ul style="list-style-type: none"> (480) Multi-Tap Ballast Factory wired at 277v unless otherwise specified.	Open <ul style="list-style-type: none"> (O) Grid <ul style="list-style-type: none"> (G) Lid <ul style="list-style-type: none"> (L) 	Bronze <ul style="list-style-type: none"> (BZ) White <ul style="list-style-type: none"> (WT) Black <ul style="list-style-type: none"> (BK) Custom Color <ul style="list-style-type: none"> (CC) Consult Factory	Qtz Re-strike <ul style="list-style-type: none"> (QR) E. Ballast <ul style="list-style-type: none"> (EB) Single Fuse <ul style="list-style-type: none"> (SF) Double fuse <ul style="list-style-type: none"> (DF) Photocell 120 Thru 277 <ul style="list-style-type: none"> (PC__)

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions